

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://dynamica.nt-rt.ru> || day@nt-rt.ru

Velocity 15HR – IMMEDIATE SHIPPING IN AMERICA



The Dynamica Velocity Micro Centrifuge V15HR satisfies the CE marking requirements to ensure safety even if a trouble occurs during operation. The tabletop centrifuge has the lowest noise level in its class (50 dB or less). The operating noise is suppressed and the sample temperature rise is prevented effectively as a result of the CAE analyses including the latest fluid analysis. Up to three sets of operating parameters can be stored. In addition, the door is equipped with the automatic door closure system. Three types of autoclavable rotors are available.

Features & Characteristics:

- Exceptionally low noise
- Safe and compact
- Easy to use
- Three autoclavable rotors

Quick Acceleration / Deceleration for more efficient operation [with FAS15E rotor]

- Acceleration: 0 to 15,000rpm (16sec.)
- Deceleration: 15,000 to 0rpm (16sec.)
- Plus coasting (free breaking) deceleration
- Max. G-force: 21,500 x g
- Max. Capacity: 2ml x 24 plus 0.5ml x 24 (Total 48 pcs of PCR tubes)
- Temp: -20 to + 40 deg. C
- Easy to use panel
- Brushless DC motor
- High RCF (max 21,500xg)
- Easy-to-use operation panel
- 3 programmed operations possible
- Selectable from 5 melodies, beep and mute

Autoclave Rotors

- Three types of autoclavable rotors are available.
- Rotors can be used for biological applications safety.

Requires 120V power supply